

Other Directive Antennas 2.3-2.6 GHz



PAN24-13G

PAN24-16G



PAR24-12



CP24-12G



CP24-24G

DESCRIPCIÓN



- Gran ancho de banda.
- Soporte robusto de fácil instalación
- Conector standard N Female (CP24-12G SMA Female)
- Herrajes incluidos

ESPECIFICACIONES

- Frecuencia 2.3 a 2.6 GHz
- Polarización Vertical / Horizontal
- Impedancia 50 Ohms
- S.W.R. < 1,5

DESCRIPTION



- Broadband Antenna.
- Easy to install.
- Standard female connector N Female (CP24-12G SMA Female)
- U-Bolts and clamps included in price

SPECIFICATIONS

- Frequency 2.3 a 2.6 GHz
- Polarization Vertical / Horizontal
- Impedance 50 Ohms
- S.W.R. < 1,5

Models	Type	Dimensions	Gain dBi	Weight (kg)	Max. Power (W)	3 dB Beamwidth
PAR24-12	Grid Parabolic	Diam. 1,20 m	27	20,00	100	6.5°
CP24-24G	Cut Grid Parabolic	0.60x0.90 m	24	2,50	100	H=10° / V=14°
CP24-12G	Small cylinder parabolic	275x90 mm	12	0,35	50	H=30° / V=60°
PAN24-8G	ABS Panel	107x94 mm	8	0,30	25	H = 30° / V = 60°
PAN24-12G	ABS Panel	275x90 mm	12	0,50	25	H = 28° / V = 70°
PAN24-16G	ABS Panel	455x135 mm	16	0,80	25	H = 27° / V = 60°
PAN24-18G	ABS Panel	265x265 mm	18	0,90	25	H = 45° / V = 75°